

ATC/IMRS4852310

1

M

*	HCMXB-2RS485-BD	V1.00	0.15W	RS485 Modbus RTU/ASCII

M

M

1.1

1.1.1

1.1.2

RUN STOP


--

*

2.2.2

24PIN	

2.2.3



4 HCMXB-2RS485-BD


		RS485
		RS485
	RS485	

2.2.4

--	--

--

2.3




3

2.1

g		15	
mm		18.6 (W) *51.1 (H)*36.1 (D)	
		0~50	
		-25~75	
		5~95%RH	
		5~95% RH	
		1m 2	
			5 ~150 Hz
			3.5mm
			1.0g
			3

	RTU/ASCII
	32
	120Ω
	9600 bps 19200 bps 38400 bps 57600 bps 115200 bps
	7 8 8
	1
	1



4.1.2




4.1.3




4.1.4

50N





50N



4.2.2



RS485



1.	RS485	120Ω	1/4
2.			
3.	RS485		

5 RS485

HCM511S



HCMXB-2RS485-BD

1

COM

1~255

11 12

- d 6í_ÆS10G•2,, .¿C •2,, .¿GVñ uG€CWC0

串口

COM11 (RS485)	COM12 (RS485)
站 号: 1	站 号: 2
波 特 率: 9600bps	波 特 率: 9600bps
协 议: (7, E, 1) ASCII	协 议: (7, E, 1) ASCII
主从模式: 主站/自由协议	主从模式: 主站/自由协议
延迟时间: 3 ms	延迟时间: 3 ms